

CAMBO

WHERE TRADITION MEETS VISION

ACTUS-XL Camera body

With the introduction of the ACTUS-XL series, Cambo's system is now extended across the Actus line of camera products. Where the Actus Mini excels in being the lightest and smallest camera platform, the ACTUS-XL system is a fusion of both the Actus and Ultima camera platforms, maintaining full camera movements.

Modular is the keyword. The Actus-XL accepts all Actus lens plates and lens adapters, sharing the same mount. On the rear standard you find an easy exchangeable frame holder for either a digital back or a DSLR/Mirrorless camera body.

Both front and rear standard have lateral movements, vertical adjustments, swings as well as tilts, all for optimised control over perspective and selective sharpness.

The default 300mm monorail is suitable for short, medium and long focal length lenses. A separate focus slider and fine focussing racks make it not only quick but very easy and precise to focus.

The compatibility with the Actus Mini platform allows the use of a variety of lens adaptors in combination with several camera bodies. These system bodies are mounted with their bayonets to the upright holder, which can rotate between landscape and portrait position within a second. This can be done without having to remove the camera body or bellows.

When using a digital back, the upright holder will accept any of the Cambo SLW-adapters. For photographers that are using digital backs without Live View, there is an adapter mount available for the Cambo sliding back. There are lens panels available for #0, #1 as well as #3 shutter systems, both mechanical and electronic lenses can be used.



ACXL-965
bayonet frame
optional bayonet



ACXL-970
digiback frame
optional adapter



ACTUS-XL Camera specs:

Overall size length / width / height: 310 x 145 x 340 mm (incl. lenspanel holder and digital back holder)
310 x 145 x 315 mm (incl. lenspanel holder and camera body holder)

Overall weight including mount: 4,8 kg (incl. lenspanelholder and frame holder)

Horizontal lateral movement: 50 mm (25/25) both on front and rear
Vertical movement: 40 mm (20/20) both on front and rear
Tilt : +20° / -20° both on front and rear
Swing : +20° / -20° both on front and rear
Coarse focussing range: 120 mm (max. extension 160 mm with default rail)
Fine focussing range: 40 mm both front and rear

Available digital back adapters: SLW-80 Hasselblad-V
SLW-89 Hasselblad-H
SLW-81 Leaf Afi/Sinar HY6
SLW-83 PhaseOne XF/DF /Mamiya AFd
SLW-87 Contax 645

Available system camera bayonets: AC-780 Canon-Eos series
AC-781 Canon-M series
AC-783 Nikon-F series
AC-785 Leica-M series
AC-786 Sony-E series
AC-787 Pentax-K series
AC-788 MicroFourThird cameras
AC-789 Olympus-OMD series
AC-790 Fuji-X series
ACXL-966 Rear mount incl. Fujifilm GFX bayonet

Ordering information: ACTUS-XL-DB Camera Body: 99010982 (incl.bellows and holders)
ACTUS-XL-35 Camera Body: 99010984 (incl.bellows and holders)

A choice of additional accessories:

Lens plates: ACB-0/ACB-1/ACB-3 - ACB-ALP/ACB-WRS
Lens adapting plates: ACB-39/ACB-HA/ACB-RZ/ACB-CA/ACB-NF/ACB-LR/ACB-M645/ACB-P645
Actar lenses: ACTAR-24, ACTAR-60, ACTAR-80, ACTAR-90, ACTAR-105, ACTAR-120
Bellows WA or Macro: AC-212/AC-216 - ACBD-252/ACDB-256
Monorail Extensions: ULM-15/ULM-25/ULM-42
Compendium: AC-343
Conversion frames: ACXL-965 for Bayonet / ACXL-970 for digiback

-for more accessories and more information about accessories see: www.cambo.com



CAMBO Fotografische Industrie BV
Haatlanderdijk 45 - P.O.Box 200
NL-8260 AE Kampen
The Netherlands

Tel : +31(0)38 3314644
Fax : +31(0)38 3315110
Email: info@cambo.com
Web : www.cambo.com